California Department of Public Health Product WorkSheet					
Manufacturing Company Information	Product Brand:	Pentek			
Pentair Residential Filtration, LLC					
5730 N. Glen Park Road	Product Model:	FPS-20 System			
Milwaukee, Wisconsin 53209	CDPH registration #	13-2207			
Phone: (262)-238-4400	Replacement Cartridge	FloPlus-20			

Operating Parameters	SI Units	Metric Units	
Service Flow Rate	10.0 gpm	37.8 lpm	
System Capacity	Х	Х	
Pressure	30-125 psi	2.1 - 8.6 Kg/cm ²	
Temperature	40-100°F	4.4-37.8°C	
	Inlet Water Quality Limits		
Turbidity	5 NTU Max.		

Website: www.pentairaqua.com

Pentek FPS-20 System Performance Data Sheet							
Contaminat Reduction Claims	Challenge Concentration	Maximum Permissible Product Water Concentration	Reduction Requirements	Reduction Average			
Cyst	Minimum 50,000/mL		≥ 99.95%	99.99%			

Note: The manufacturer is required to re-test the product every 5 years for material safety, structural integrity and all performance claims made. Any change to the product must be submitted to the certification agency for a technical review. Testing may be required sooner based on the technical review.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Note: The system must be installed and maintained according to manufacturer's recommendations, including replacement of filter cartridges. The contaminants or other substances removed or reduced by this system are not necessarily in your water. Please see Product Installation manual for details.